



Metrisch (4150 & 6200 bar) / Metric (60,000 & 90,000 psi)

	Artikel-Nr.	Typ	Type	A	B	C	D	E (Depth)	F	G
1/4"	101414	Gerade	straight	40	18	SW / AF 22	-	-	SW / AF 17	M16 x 1.5
	201414	Winkel	elbow	32	11	26	5	20	SW / AF 17	M16 x 1.5
	301414	T-Stück	tee	32	10	32	11	20	SW / AF 17	M16 x 1.5
	401414	Kreuzstück	cross	44	22	32	10	20	SW / AF 17	M16 x 1.5
3/8"	103838	Gerade	straight	48	18	SW / AF 27	-	-	SW / AF 22	M20 x 1.5
	203838	Winkel	elbow	48	20	35	7	25	SW / AF 22	M20 x 1.5
	303838	T-Stück	tee	50	20	40	12	25	SW / AF 22	M20 x 1.5
	403838	Kreuzstück	cross	54	24	50	20	25	SW / AF 22	M20 x 1.5
9/16"	109191	Gerade	straight	54	14	SW / AF 41	-	-	SW / AF 32	M30 x 2
	209191	Winkel	elbow	65	25	52	12	40	SW / AF 32	M30 x 2
	309191	T-Stück	tee	65	25	65	25	40	SW / AF 32	M30 x 2
	409191	Kreuzstück	cross	80	40	65	25	40	SW / AF 32	M30 x 2

Imperial (4150 bar) / imperial (60,000 psi)

	Artikel-Nr.	Typ	Type	A	B	C	D	E (Depth)	F	G
1/4"	101414-I	Gerade	straight	35	12	SW/AF 19	-	-	AF 5/8"	9/16" - 18 UNF
	201414-I	Winkel	elbow	38	10.8	25	4.5	19	AF 5/8"	9/16" - 18 UNF
	301414-I	T-Stück	tee	50	27	32	11	25	AF 5/8"	9/16" - 18 UNF
	401414-I	Kreuzstück	cross	50	27	32	9	25	AF 5/8"	9/16" - 18 UNF
3/8"	103838-I	Gerade	straight	44	12	SW/AF 27	-	-	AF 13/16"	3/4" - 16 UNF
	203838-I	Winkel	elbow	50	15.5	38	9.4	25	AF 13/16"	3/4" - 16 UNF
	303838-I	T-Stück	tee	50	18	40	11	25	AF 13/16"	3/4" - 16 UNF
	403838-I	Kreuzstück	cross	50	18	54	22	25	AF 13/16"	3/4" - 16 UNF
9/16"	109191-I	Gerade	straight	56	16	SW/AF 36	-	-	AF 1 3/16"	1 1/8" - 12 UNF
	209191-I	Winkel	elbow	67	28	48	8.5	40	AF 1 3/16"	1 1/8" - 12 UNF
	309191-I	T-Stück	tee	67	27	54	15	40	AF 1 3/16"	1 1/8" - 12 UNF
	409191-I	Kreuzstück	cross	67	27	70	30	40	AF 1 3/16"	1 1/8" - 12 UNF